



## Klime-ezee Mobile Safety Steps



All the Klime-ezee Mobile Safety Steps are fitted with rubber-tyred wheels and castors, providing easy control and mobility. The steps can be moved with a force of only 5-10kg. This is well below the 25kg force determined by the Health & Safety Executive.

The steps below are supplied as Standard with Double Handrails and Punched Steel treads

- ◆ Access barred retractable brake
- ◆ Full height handrail
- ◆ Ample platform area
- ◆ Kick plates all round (KE7 - KE15)
- ◆ Punched metal treads
- ◆ Retractable swivel castors
- ◆ Rubber tyred wheels & castors
- ◆ Large steel feet (KE7 & KE15)
- ◆ ERW steel tube to British Standards
- ◆ Safe working load 300kg

### Specification for the Klime-ezee Industrial Mobile Safety Steps

- ◆ Tread Size: 550mm x 200mm
- ◆ Platform Size: 550mm x 400mm
- ◆ Frame: 25mm diameter Tube
- ◆ Fitted with Rubber Tyred wheels & castors

**PLEASE NOTE: THESE STEPS ARE MADE TO ORDER, THEREFORE OVERNIGHT DELIVERY IS NOT AVAILABLE ON THESE ITEMS**

CODE	No OF TREADS	PLATFORM HEIGHT	WORKING HEIGHT	OVERALL HEIGHT	OVERALL WIDTH	OVERALL LENGTH	WEIGHT
KE05	5	1250mm	2250-3000mm	2250mm	835mm	1270mm	55kg
KE06	6	1500mm	2500-3250mm	2500mm	835mm	1360mm	62kg
KE07	7	1750mm	2750-3500mm	2750mm	850mm	1450mm	70kg
KE08	8	2000mm	3000-3750mm	3000mm	850mm	1575mm	78kg
KE09	9	2250mm	3250-4000mm	3250mm	850mm	1730mm	90kg
KE10	10	2500mm	3500-4250mm	3500mm	1000mm	1905mm	98kg
KE11	11	2750mm	3750-4500mm	3750mm	1000mm	2070mm	105kg
KE12	12	3000mm	4000-4750mm	4000mm	1000mm	2230mm	116kg
KE12	13	3250mm	4250-5000mm	4250mm	1230mm	2470mm	125kg
KE14	14	3500mm	4500-5250mm	4500mm	1230mm	2630mm	130kg
KE15	15	3750mm	4750-5500mm	4750mm	1320mm	2795mm	138kg

**Free Standard Delivery within 10-15 working days (Mon to Fri)**