LYTE INDUSTRIAL FOLDING TOWER SYSTEM - LIFT



Browns Ladders Ltd



| PLATFORM HEIGHT MAX | 0.6M | 1.6M | 2.1M | 3.1M | 3.6M | 4.6M | 5.1M | 6.1M |
|----------------------------------|------|------|------|------|------|------|------|------|
| 125mm Dual Locking Castors | 4 | 4 | 4 | 4 | 4 | 4 | 4 | 4 |
| Base Unit | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| 1m Additional Frame | - | 2 | - | 2 | - | 2 | 2 | - |
| 1.5m Additional Frame | - | - | 2 | 2 | 4 | 4 | 2 | 2 |
| 2m Additional Frame | - | - | - | - | - | - | 2 | 4 |
| 1.8m Additional Hatch Deck Hatch | 1 | 1 | 1 | 2 | 2 | 2 | 2 | 3 |
| 1.8m Horizontal Brace | 4 | 5 | 5 | 9 | 9 | 9 | 9 | 13 |
| 2.1m Diagonal Brace | - | 1 | 2 | 3 | 3 | 4 | 5 | 6 |
| 1.8m Toeboard Length | - | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| Toeboard Single Width | - | 2 | 2 | 2 | 2 | 2 | 2 | 2 |
| Standard Stabiliser | - | - | 4 | 4 | 4 | - | - | - |
| Telescopic Stabiliser | - | - | - | - | - | 4 | 4 | 4 |

The LIFT system was introduced to the welded product range in 2004 as a result of popular demand and to satisfy the need for a smaller industrial tower for smaller access solutions.

- Base can be used alone or increased using extra components to achieve 7 additional heights
- Manufactured, tested & certified to BS EN1004-1:2020
- Fits easily into most small vans or estate cars
- Quick and easy to erect saving time on each job
- Narrow width compact & easy storage
- Spring-loaded claws on all bracings
- Smooth & ribbed texture on braces for quick identification
- 3T compatible







Tel: 01282 615517 Email: sales@brownsladders.co.uk

www.brownsladders.co.uk